

SK-D3309-Pro LCD Digital 3D Shaker

Features

- Three-dimensional rocking motion with an angle of 9°
- Max. load capacity is 5kg with platform
- Speed range of 10-70rpm
- Double LCDs for independent display of time and speed
- Various of platform accessories



Timer




Wide range of accessories

SK-D1807-S LED Digital 3D Shaker

Features

- Three-dimensional rocking motion with the angle of 7°
- Max. load capacity is 3kg with platform
- Speed range of 10-80rpm
- Double LEDs for independent display of time and speed
- Various of platform accessories





Specifications

	SK-D3309-Pro	SK-D1807-S
Tilt angle	9°	7°
Max. load capacity (with platform)	5kg	3kg
Motor type	DC motor	DC motor
Motor input power	40W	16W
Motor output power	24W	10W
Speed range	10-70rpm	10-80rpm
Speed display	LCD	LED
Timer display	LCD	LED
Time settings range	1min-19h59min	1min-19h59min
Voltage	100-240V, 50/60Hz	100-240V, 50/60Hz
Power	50W	20W
Weight	9kg	2.7kg
Permissible ambient temperature and humidity	5-40°C, 80%RH	5-40°C, 80%RH
Dimension[WxDxH]	360x430x106mm	270x330x130mm
Protection class	IP21	IP21
Data connector	-	-