

SK-L330-Pro SK-L180-Pro LCD Digital Linear Shaker

Features

- Max. load capacity is 7.5kg(L330) and 2.5kg(L180) with platform
- Double LCDs for independent display of time and speed
- Wide range of platforms for use with a variety of vessels
- Maintenance-free brushless DC motor
- Over speed detection and protection



Timer




Wide range of accessories

SK-L180-S LED Digital Linear Shaker

Features

- Max. load capacity is 3kg with platform
- Double LEDs for independent display of time and speed
- Speed range of 40-200 rpm
- Wide range of platforms for use with a variety of vessels





| Specifications | SK-L330-Pro | SK-L180-Pro | SK-L180-S |
|--|--------------------|--------------------|-------------------|
| Amplitude | 10mm | 4mm | 20mm |
| Max. load capacity (with platform) | 7.5kg | 2.5kg | 3kg |
| Motor type | Brushless DC motor | Brushless DC motor | DC motor |
| Motor input power | 28W | 28W | 16W |
| Motor output power | 15W | 15W | 10W |
| Speed range | 100-350rpm | 100-350rpm | 40-200rpm |
| Speed display | LCD | LCD | LED |
| Timer display | LCD | LCD | LED |
| Time settings range | 1min-19h59min | 1min-19h59min | 1min-19h59min |
| Voltage | 100-240V, 50/60Hz | 100-240V, 50/60Hz | 100-240V, 50/60Hz |
| Power | 30W | 30W | 20W |
| Weight | 13.5kg | 8.1kg | 3.1kg |
| Permissible ambient temperature and humidity | 5-40°C, 80%RH | 5-40°C, 80%RH | 5-40°C, 80%RH |
| Dimension[WxDxH] | 370x420x100mm | 300x340x100mm | 270x330x110mm |
| Protection class | IP21 | IP21 | IP21 |
| Data connector | RS232 | RS232 | - |

