

DLAB DM0506 low-speed centrifuge, supplied with built in fixed angle rotor A6-15P which can hold up to 15mL/10mL/7mL/5mLx6 tubes. It is widely used for blood or urine separation in medical routine practice in hospitals, clinics or research institutes.

DM0506 Low-speed Centrifuge

New

Features

- Speed range from 300-5000rpm;
- Rotor speed can be set and displayed by RPM or G-force;
- Defined program by knob will be stored and activated when power on;
- Two programs P1/P2, easy to start the procedure by one key;
- Two deceleration speeds setting to meet different requirements;
- Easy-to-read processing display and sound alert;
- Automatic lid-lock release after running;
- Maintenance-free brushless DC motor.



Specifications

| | DM0506 |
|---------------------------|--|
| Speed Range | 300-5000rpm, increment:10rpm |
| Max. RCF | 2350xg, increment: 10g |
| Speed accuracy | ±20rpm |
| Rotor capacity | 6x15mL/10mL/7mL/1.5-5ml |
| Run Time | 30sec-99min, HD(continuous running) |
| Display | LCD |
| Programs Memory | 2 |
| Acceleration/Deceleration | 1 ↑ 2 ↓ |
| Safety Devices | Door interlock, Overspeed detector, Automatic internal diagnosis |
| Motor | Brushless DC motor |
| Power | Single-phase, 100V-240V,50Hz/60Hz, 70W |
| Dimension(WxDxH) | 300X240X180mm |
| Weight | 5.2kg |

Advanced features

Speed/RCF switch; sound-alert function

Available adapters



A5P17 Cat. No.19500022

5ml adapter, Adapted to 13×75mm blood collection tube



A2P17 Cat. No.19500023

1.5/2ml Cryogenic Vials/ centrifuge tube adapter

Low-speed Centrifuges